

Global Parts Order Processing  
Material Safety Data Sheet  
NORTHAMPTON COMM. COLLEGE

November 7, 2017  
08:29

C H R Y S L E R  
HAZARD COMMUNICATION SHEET

127444 PART/COMMTY CD: 04886330AA *P/N*  
PREPARATION DATE: 03-02-07 STNDRD: N/AV SUPPLIER: 37637 MFGR: 03500  
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

\*\*\* SECTION 01 - PRODUCT INFORMATION \*\*\*

MFG BY: PART SALES & SERVICE FCA US LLC  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
DIST BY: PART SALES & SERVICE FCA US LLC  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
FCA US LLC INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888  
BRAND NAME: MOPAR SUPER KLEEN  
MFG ID : 83195  
DESCRIPTION: CLEANER-ALL PURPOSE *super Kleen*

\*\*\* SECTION 02 - INGREDIENTS \*\*\*

HAZARDOUS INGREDIENTS: PERCENT  
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS  
\*\*\*EXISTING INGREDIENTS\*\*\*  
ODORLESS MINERAL SPIRITS 60-100 W 300 300 100 PPM  
064741-65-7 NAPHTHA, PETROLEUM, L 400 N/AP 400  
GENERIC DESC: PETROLEUM DISTILLATE(S).

\*\*\* SECTION 03 - PHYSICAL DATA \*\*\*

BOILING POINT : 355 TO 395 F SOLUB IN WATER: NEGLIGIBLE ( < 0.1% )  
VAPOR PRESSURE: 2 MM HG AT 100 F EVAP. RATE: < 0.100 REF: BUTYLACETATE  
VAPOR DENSITY : 5.300 AT N/AV SPECIFIC GRAVITY: 0.759 AT N/AV  
PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV  
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: 6.24000 LB/GAL  
ODOR THRESHOLD: N/AV PPM FOR % POPULATION  
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV  
APPEARANCE & ODOR: APPEARANCE: LIGHT..... STATE: LIQUID..... ODOR:  
HYDROCARBON.....

\*\*\* SECTION 04 - FIRE AND EXPLOSION DATA \*\*\*

FLASH POINT: 125 F TCC IGN TEMP: N/AV LEL: 1.000% UEL: 7.000%  
SPECIAL FIRE & EXPLOSION HAZARDS:

COMBUSTIBLE. MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS. EXPOSURE TO  
INTENSE HEAT AND DIRECT FLAME MAY RESULT IN PRESSURE BUILD-UP IN CONTAINER,  
CAUSING WEAKENING OR RUPTURING OF THE CONTAINER. KEEP CONTAINERS TIGHTLY



**Global Parts Order Processing  
Material Safety Data Sheet  
NORTHAMPTON COMM. COLLEGE**

November 7, 2017  
08:29

CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR CONTAINER (EVEN EMPTY) BECAUSE PRODUCT (OR RESIDUE) CAN IGNITE EXPLOSIVELY. MAY REACT WITH OXIDIZERS.

**EXTINGUISHING MEDIA:**

WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

**SPECIAL FIREFIGHTING PROCEDURES:**

AVOID BREATHING VAPOR OR FUMES. USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS. DO NOT USE WATER IN STRAIGHT STREAMS. USE WATER TO COOL FIRE EXPOSED CONTAINERS. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

SENSITIVE TO MECHANICAL IMPACT?: NO

SENSITIVE TO STATIC DISCHARGE?: YES

**HAZARDOUS COMBUSTION PRODUCTS:**

CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AP

-----  
**\*\*\* SECTION 05 - HEALTH HAZARD DATA \*\*\***  
-----

**EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:**

<<---INHALATION--->> HIGH CONCENTRATION MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION OR DERMATITIS. PROLONGED CONTACT-SKIN CONTACT MAY PRODUCE DEFATTING AND DRYING OF SKIN. <<---EYE CONTACT--->> PROLONGED CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION AND TEARING. <<---INGESTION--->> MAY BE HARMFUL IF SWALLOWED. MAY CAUSE UPSET STOMACH, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION (GOING DOWN THE WRONG PIPE INTO THE WINDPIPE) MAY CAUSE THE FOLLOWING: CHEMICAL PNEUMONITIS (AN INFLAMMATION OF THE LUNGS SIMILAR TO PNEUMONIA, WHICH IS CAUSED BY GETTING THE LIQUID FORM OF A CHEMICAL INTO THE LUNGS).

**EMERGENCY FIRST AID PROCEDURES:**

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF PULMONARY SYMPTOMS DEVELOP, CONSULT A PHYSICIAN. IF BREATHING IS DIFFICULT, GIVE OXYGEN. ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. IMMEDIATELY FLUSH CONTAMINATED AREA WITH LARGE AMOUNTS OF WATER. WASH WITH SOAP AND WATER. APPLY SKIN CREAM IF DEFATTING OF SKIN OCCURS. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---EYE CONTACT--->> REMOVE CONTACT LENSES TO ASSURE COMPLETE FLUSHING. RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT LIQUID FROM SEEPING INTO THE WINDPIPE AND LUNGS. IF VICTIM IS DROWSY OR UNCONSCIOUS, PLACE ON THE LEFT SIDE WITH THE HEAD DOWN. DO NOT GIVE ANYTHING BY MOUTH.



**Global Parts Order Processing  
Material Safety Data Sheet  
NORTHAMPTON COMM. COLLEGE**

November 7, 2017  
08:29

\*\*\* SECTION 06 - REACTIVITY DATA \*\*\*

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE, SPARKS OR OPEN FLAME.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION MAY PRODUCE THE FOLLOWING: CARBON MONOXIDE AND CARBON DIOXIDE.

\*\*\* SECTION 07 - SPILL OR LEAK PROCEDURES \*\*\*

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WIPE UP OR SCRAPE UP SMALL SPILL OR RESIDUE. LARGE SPILL-ELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). WEAR PROTECTIVE CLOTHING. WEAR RESPIRATORY PROTECTION. SHUT OFF SOURCE OF LEAK IF POSSIBLE. CONTAIN WITH EARTH OR SAND TO PREVENT ENTERING DRAINS. USE WATER SPRAY TO ELIMINATE VAPOR. VENTILATE AREA, ESPECIALLY LOW PLACES WHERE HEAVY VAPOR MIGHT COLLECT. ABSORB ON AN INERT MATERIAL AND REMOVE WITH NON-SPARKING TOOLS. DISCARD INTO SEALED CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS.

\*\*\* SECTION 08 - SPECIAL PROTECTION \*\*\*

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. IF THE ALLOWABLE LIMIT OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, USE THE FOLLOWING: ORGANIC VAPOR RESPIRATOR, AIR-SUPPLIED RESPIRATOR.

VENTILATION TYPE:

TO MAINTAIN THE TLV, THE FOLLOWING MAY BE NEEDED: GOOD GENERAL VENTILATION OR LOCAL EXHAUST VENTILATION. VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF.

PROTECTIVE GLOVES:

RECOMMENDED. NEOPRENE GLOVES OR NITRILE RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES OR CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE REUSE. TO AVOID PROLONGED SKIN CONTACT, USE THE



**Global Parts Order Processing  
Material Safety Data Sheet  
NORTHAMPTON COMM. COLLEGE**

November 7, 2017  
08:29

FOLLOWING: CLOTHING (SAME MATERIAL AS GLOVES).

\*\*\* SECTION 09 - SPECIAL PRECAUTIONS \*\*\*

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

COMBUSTIBLE. STORE IN EXPLOSION RESISTANT/FLAMMABLE LIQUID STORAGE ROOM. STORE IN A WELL VENTILATED AREA. STORE SEPARATE FROM INCOMPATIBLE MATERIALS. USE WITH ADEQUATE VENTILATION. KEEP FROM HEAT, SPARK OR OPEN FLAMES. BOND AND GROUND ALL CANS, DRUMS, MIXERS ETC. TO PREVENT STATIC SPARKS. TAKE "NO SMOKING" PRECAUTIONS. REACTS WITH OXIDIZERS. DO NOT CUT EMPTY CONTAINER WITH A TORCH. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. GROUND CONTAINERS WHEN POURING. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID). DO NOT REUSE CONTAINER FOR ANY PURPOSE UNTIL IT HAS BEEN COMMERCIALY CLEANED.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING MIST. AVOID BREATHING VAPOR. AVOID SKIN CONTACT. AVOID EYE CONTACT. AVOID INGESTION. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY AFTER USING. WASH THOROUGHLY AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

\*\*\* SECTION 10 - WASTE LABELING INFORMATION \*\*\*

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: UN1268 ERG#: 128 HAZARD CLASS - PRMY: 3 PACKING GROUP: III

<\*> REFER TO EXPLANATIONS PAGE - ITEM D.O.T. FLAMMABLE LIQUIDS.

PROPER SHIPPING NAME: WASTE PETROLEUM DISTILLATES, N.O.S.

LABEL(S) REQUIRED: FLAMMABLE LIQUID

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD: D001/I ; MICH:

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT NEEDED

